

# SAFETY DATA SHEET

## SPOTMASTER GEL XP

### SECTION 1- PRODUCT IDENTIFICATION

**PRODUCT NAME** : SPOTMASTER GEL XP  
**SYNONYMS** : Product is a mixture: No synonyms are available.  
**PRODUCT USE** : Flammable Material  
**SUPPLIER** : HYDRAMASTER CORP.  
**SUPPLIER'S ADDRESS** : 11015 47TH AVE. W, MUKILTEO, WA 98275  
(425) 775-7272  
**EMERGENCY RESPONSE PHONE NUMBER** : PERS: 1-800-633-8253

### SECTION 2 – HAZARD IDENTIFICATION

#### CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

**GHS U.S. – CLASSIFICATION** : H302 Harmful if swallowed.  
H315 Causes skin irritation  
H319 Causes serious eye irritation

**LABEL ELEMENTS** : **GHS – US HAZARD PICTOGRAMS** The product is classified and labeled according to the Globally Harmonized System (GHS).

**HAZARD PICTOGRAMS** :



**SIGNAL WORD** : DANGER

#### HAZARD STATEMENTS (GHS-US)

: H225 Highly flammable liquid and vapor  
: H302 Harmful if swallowed.  
: H315 Causes skin irritation.  
: H319 Causes serious eye irritation.  
: H336 May cause drowsiness or dizziness.

**Note** : Acetone Acute Toxicity Dermal: Contains 100 % of the mixture consists of ingredient(s) of unknown toxicity.  
Acute Toxicity Inhalation Gas: Contains 100 % of the mixture consists of ingredient(s) of unknown toxicity.  
Acute Toxicity Inhalation Vapor: Contains 100 % of the mixture consists of ingredient(s) of unknown toxicity.  
Acute Toxicity Inhalation Dust/Mist: Contains 100 % of the mixture consists of ingredient(s) of unknown toxicity.

#### PRECAUTIONARY STATEMENTS (SGS-US)

**PREVENTION** : P101 If medical advice is needed, have product container or label at hand.  
: P102 Keep out of reach of children.  
: P103 Read label before use.  
: P210 Keep away from heat/sparks/open flames/hot surfaces – No smoking.  
: P233 Keep container tightly closed.  
: P240 Ground/bond container and receiving equipment.  
: P241 Use explosion proof electrical/ventilation/light...equipment  
: P242 Use only non-sparking tools.  
: P243 Take precautionary measures against static discharge.  
: P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

## SAFETY DATA SHEET SPOTMASTER GEL XP

	: P264	Wash skin and contaminated clothing thoroughly after handling.
	: P270	Do not eat, drink or smoke when using this product.
	: P271	Use only outdoors or in a well ventilated area.
	: P280	Wear suitable protective gloves/protective clothing/eye protection/face protection.
<b>RESPONSE</b>	: P305+P351 +P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.
	: P337+P313	If eye irritation persists, get medical attention.
	: P303+P361 +351	IF ON SKIN: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
	: P304+P340	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable to breathing.
	: P337+P313	If eye irritation persists: Get medical advice/attention.
<b>STORAGE</b>	: P403+P233	Store in a well ventilated place. Keep container tightly closed.
	: P403+P235	Store in a well ventilated place. Keep cool.
	: P405	Store locked up.
<b>DISPOSAL</b>	: P501	Dispose of contents/container in accordance with local/regional/national/international regulations
<b>OSHA HAZARDS</b>	: Isopropanol:	Flammable liquid, Target Organ Effect, Irritant
<b>TARGET ORGANS</b>	: Isopropanol:	Cardiovascular system, Gastrointestinal tract, Kidney, Liver, Nerves.
	:	
<b>CLASSIFICATION SYSTEM</b>	: NFPA/HMIS Definitions:	0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme.
<b>NFPA RATINGS (SCALE 0-4)</b>	: Health = 2, Fire = 2, Reactivity = 0	
<b>HMIS RATINGS (SCALE 0-5)</b>	: Health = 2, Fire = 2, Reactivity = 0	

### SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

<b>CHEMICAL CHARACTERISTIC</b>	: Mixtures
<b>DESCRIPTION</b>	: Mixture of the substances listed below with nonhazardous additions.

COMPONENT	PERCENT	CAS #	EC #	GHS CLASS
Acetone	20-40	67-64-1	200-662-2	Flam Liq Cat 2, Eye Dam Cat 2 Acute Aquatic Cat 2
Isopropanol (Isopropyl alcohol)	1-5	67-63-0	200-661-7	Eye Irrit Cat 2, Flam Liq Cat 2 STOT SE Cat 3
Diethylene Glycol Monobutyl Ether	10-20	112-34-5	203-961-6	Eye Irrit Cat 2B

Irrit = Irritation, Cor = Corrosive, Dam = Damage, Cat = Category, Tox = Toxic, STOT = Specific Target Organ Toxicity. Also contains a non-hazardous thickening agent.

### SECTION 4 – FIRST AID MEASURES

#### DESCRIPTION OF FIRST AID MEASURES

<b>GENERAL</b>	: If you feel unwell, seek medical advice. Show the label where possible. Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area
<b>EYE CONTACT</b>	: Immediately flush eyes with low pressure water for at least 15 minutes. Hold eyelids open to ensure adequate flushing. Remove contact lenses, if present and easy to do so. Continue rinsing. If irritation persists, get immediate medical attention.
<b>SKIN CONTACT</b>	: Remove contaminated clothing and shoes. Wash affected skin area with soap and water. If irritation persists, get immediate medical attention. Wash contaminated

# SAFETY DATA SHEET

## SPOTMASTER GEL XP

- clothing before reuse.
- SWALLOWING (INGESTION)** : If ingested, dilute swallowed material by drinking water. **DO NOT INDUCE VOMITING.** If vomiting occurs spontaneously, keep airway clear and have victim lean forward to prevent aspiration. Give more water when vomiting stops. Never give anything by mouth to an unconscious person. Get immediate medical attention.
- INHALATION** : Remove to fresh air. If signs/symptoms continue, get medical attention. Give oxygen or artificial respiration as needed.
- OTHER INSTRUCTIONS** : Rescue personnel must wear appropriate protective equipment during removal of victims from contaminated areas. Treat symptomatically and supportively.

### SECTION 5 – FIRE FIGHTING MEASURES

- EXTINGUISHING MEDIA** : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
- SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS** : Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Keep unopened containers cool by spraying with water
- UNUSUAL FIRE AND EXPLOSION HAZARDS** : Vapors may travel to source of ignition and flash back.
- FLASH POINT (Acetone)** : -20°C Closed Cup.

### SECTION 6 – ACCIDENTAL RELEASE MEASURES

- PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT & EMERGENCY PROCEDURES** : Do not inhale vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. Restrict access to keep out unauthorized or unprotected personnel. Wear protective equipment. Avoid inhalation and direct contact.
- ENVIRONMENTAL PROCEDURES METHODS AND MATERIALS FOR CONTAINMENT AND CLEAN-UP** : Keep spilled material away from sewage/drainage systems and waterways.  
: All clean-up personnel must be properly trained. Confine the spill and remove incompatible materials and ignition sources. Ensure adequate ventilation. Secure the source of the leak if conditions are safe. Collect with an electrically protected vacuum cleaner or by wet-brushing and place waste in an appropriate container for disposal. Use care during clean-up to avoid exposure to the material and injury from broken containers.

### SECTION 7 – HANDLING AND STORAGE

- PRECAUTIONS FOR SAFE HANDLING** : Do not get on skin or in eyes. Do not inhale vapor or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the buildup of electrostatic charge.
- ENVIRONMENTAL PRECAUTIONS** : Stop leak. Contain spill if possible and safe to do so. Prevent product from entering drains.
- CONDITIONS FOR SAFE STORAGE** : Keep container tightly closed in a cool, dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Protect containers from heat, physical damage, ignition sources and incompatible materials. Have emergency equipment for fires and spills readily available.



# SAFETY DATA SHEET

## SPOTMASTER GEL XP

### SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

**TLV (THRESHOLD LIMIT VALUE)** : The TLV in section in section III is the ACGIH/TLV-TWA (threshold limit value/time weighted average concentration for an eight hour work day). The STEL is the short term exposure limit and the (Ceil) is the ceiling limit.

COMPONENT	OSHA PEL – TWA	ACGIH – TLV	ACGIH – STEL
Acetone	1000 ppm	500 ppm	750 ppm
Isopropanol (Isopropyl alcohol)	400 ppm	200 ppm	400 ppm
Diethylene Glycol Monobutyl Ether	Not Established	Not Established	Not Established

- EYE PROTECTION** : Use chemical safety goggles and/or a full face shield where splashing is possible. Use equipment approved by appropriate government standards, such as NIOSH (US) or EN166 (EU) Maintain eye wash fountain and quick-drench facilities in work area.
- SKIN PROTECTION** : Wear impervious, flame retardant, antistatic protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
- RESPIRATORY PROTECTION** : Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).
- HAND PROTECTION** : Handle with gloves. Gloves must be inspected prior to use. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.
- APPROPRIATE ENGINEERING CONTROLS** : General room or local exhaust ventilation is usually required to meet exposure limit(s). Electrical equipment should be grounded and conform to applicable electrical code.
- ADDITIONAL MEASURES** : Emergency eyewash and safety shower facilities should be available in the immediate work area.
- REQUIRED WORK/HYGIENE** : Wash hands thoroughly after handling. Keep away from all food stuffs, beverages and feed. Do not eat, drink or smoke in work area.

### SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

- APPEARANCE** : Opaque gel with solvent odor.
- ODOR** : Mild odor
- ODOR THRESHOLD** : Not available
- PH** : 7-9 aqueous solution
- MELTING POINT/FREEZING POINT** : Not available
- BOILING POINT** : Approx. 56° F. (Acetone 100%)
- FLASH POINT** : -20°C, (-4°F) (Acetone 100%)
- EVAPORATION RATE** : Not available
- FLAMMABILITY** : Flammable Liquid
- LOWER FLAMMABILITY LIMIT** : 2.6% (Acetone)
- UPPER FLAMMABILITY LIMIT** : 12.8% (Acetone)
- VAPOR PRESSURE** : Not available
- VAPOR DENSITY (AIR=1)** : Not available
- RELATIVE DENSITY** : 0.85
- SOLUBILITY IN WATER** : Soluble in water
- PARTITION COEFFICIENT n-OCTANOL/WATER** : Not available

## SAFETY DATA SHEET

### SPOTMASTER GEL XP

**AUTOIGNITION TEMPERATURE** : Not available  
**DECOMPOSITION TEMPERATURE** : Not available

#### SECTION 10 – STABILITY AND REACTIVITY

**STABILITY** : Stable under recommended storage conditions.  
**HAZARDOUS CONDITIONS TO AVOID** : Heat, flames, and sparks. Extreme temperatures and direct sunlight.  
**INCOMPATIBLE MATERIALS** : Oxidizing agents, Acid anhydrides, Aluminium, Halogenated compounds, Acids.  
**HAZARDOUS DECOMPOSITION PRODUCTS** : Carbon oxides are expected to be, under fire conditions, the primary hazardous decomposition products.

#### SECTION 11 – TOXICOLOGICAL INFORMATION

**TOXICOLOGICAL INFORMATION** : **Acetone**  
**ACUTE TOXICITY** : LD50 Oral (rat): 5800 mg/kg. LD50 Dermal (rabbit): 20,000 mg/kg. LC50 Inhalation (rat) 8hr: 50.1 mg/L.  
**MUTAGENICITY** : No evidence of a mutagenic effect.  
**TERATOGENICITY** : Evidence of a teratogenic effect.  
**SENSITIZATION** : No evidence of a sensitizing effect.  
**TARGET ORGAN EFFECTS: ACUTE & CHRONIC** : Acute: Central Nervous System, Cardiovascular System. Chronic: Male reproductive System.

**TOXICOLOGICAL INFORMATION** : **Isopropanol (Isopropyl Alcohol)**  
**ACUTE TOXICITY** : LD50 Oral (rat): 5045 mg/kg. LD50 Dermal (rabbit): 12,800 mg/kg. LC50 Inhalation (rat) 8hr: 16,000 mg/kg.

**OTHER INFORMATION EYES** : Produces irritation, characterized by a burning sensation, redness, tearing, inflammation, and possible corneal injury. May cause transient corneal injury

**OTHER INFORMATION INGESTION** : Causes gastrointestinal irritation with nausea, vomiting and diarrhea. May cause kidney damage. May cause central nervous system depression, characterized by excitement, followed by headache, dizziness, drowsiness, and nausea.

**OTHER INFORMATION INHALATION** : Inhalation of high concentrations may cause central nervous system effects characterized by nausea, headache, dizziness, unconsciousness and coma. May cause narcotic effects in high concentration. Causes upper respiratory tract irritation. Inhalation of vapors may cause drowsiness and dizziness.

**OTHER INFORMATION SKIN** : May cause irritation with pain and stinging, especially if the skin is abraded. Isopropanol has a low potential to cause allergic skin reactions; however, rare cases of allergic contact dermatitis have been reported.

**STOT SINGLE EXPOSURE CARCINOGENICITY** : Inhalation - May cause drowsiness or dizziness. - Central Nervous System.  
: IARC: Group 3: Not classifiable as to its carcinogenicity to humans. No component of this product, present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH, NTP or OSHA.

**TOXICOLOGICAL INFORMATION** : **Diethylene Glycol Monobutyl Ether**  
**ACUTE TOXICITY** : Oral LD50 Oral (rat): 5560 mg/kg. LC50 dermal and inhalation: Not listed.  
**CHRONIC EFFECTS** : Prolonged absorption causes liver and kidney damage, and red cell haemolysis (blood in urine) in laboratory animals; no such effects have been seen in humans  
**SENSITISATION** : Not a sensitizer.  
**CARCINOGENICITY** : No component of this product present at levels greater than or equal to 0.1% is identified as probable or confirmed human carcinogen by IARC, ACGIH, NTP, and OSHA.

# SAFETY DATA SHEET

## SPOTMASTER GEL XP

### SECTION 12 – ECOLOGICAL INFORMATION

<b>ECOLOGICAL INFORMATION OVERVIEW</b>	: <b>Acetone</b>
	: Moderate ecological hazard. This product may be dangerous to plants and/or wildlife.
<b>MOBILITY</b>	: This material is expected to have very high mobility in soil. It does not absorb to most soil types.
<b>PERSISTENCE</b>	: No data available.
<b>BIODEGRADABILITY</b>	: Biodegrades quickly.
<b>ECOTOXICITY</b>	: 96 HR LC50 ONCORHYNCHUS MYKISS 4.74 - 6.33 ml/l 96 HR LC50 LEPOMIS MACROCHIRUS 8300 MG/L 48 HR EC50 DAPHNIA MAGNA 12600 - 12700 MG/L
<b>ECOLOGICAL INFORMATION</b>	: <b>Isopropanol</b>
<b>ACUTE FISH TOXICITY</b>	: LC50 / 96 hr: Pimephales promelas: 9,640 mg/L.
<b>TOXICITY TO DAPHNIA</b>	: EC50 / 24 h / Water Flea - 5,102 mg/L.
<b>TOXICITY TO PLANTS</b>	: EC50 / 72 hours Desmodosmus subspicatus > 2,000 mg/L.
<b>MOBILITY</b>	: This material is expected to have very high mobility in soil. It does not absorb to most soil types.
<b>PERSISTENCE AND DEGRADABILITY</b>	: No data available.
<b>BIOACCUMULATIVE POTENTIAL</b>	: No data available.
<b>ECOLOGICAL INFORMATION</b>	: <b>Diethylene Glycol Monobutyl Ether</b>
<b>ECOTOXICITY</b>	: This product cannot accumulate in living tissue; diluted, this product is readily and rapidly in a wastewater treatment facility; in BOD test, 88% degraded in 28 says; half-life in air estimated as 10 hours.
<b>PERSISTENCE AND DEGRADABILITY</b>	: No data available.

### SECTION 13 – DISPOSAL CONSIDERATIONS

<b>WASTE DISPOSAL</b>	: This product must be disposed of in accordance with Federal, state and local environmental regulations. Discarded materials may be considered hazardous waste due to pH/corrosivity. It is the responsibility of the product user to determine at the time of disposal whether a material containing, or derived from this product, should be classified as a hazardous waste.
-----------------------	--

### SECTION 14 – TRANSPORTATION INFORMATION

<b>DOT/IMDG/ IATA PROPER SHIPPING NAME</b>	: UN-1993, Flammable Liquid, N.O.S. (Contains Acetone) 3, PG-II <b>Note:</b> Containers of Spotmaster Gel XP may be transported by ground only in the continental United States as a "limited quantity" if the individual container is less than 1 liter. Otherwise, this product must be shipped as a flammable liquid.
<b>HAZARD CLASS AND LABEL</b>	: 3 (Flammable Liquid)
<b>UN NUMBER</b>	: UN-1993
<b>PACKAGING GROUP</b>	: PG-II
<b>EPA REPORTABLE QUANTITY (RQ)</b>	: Not Applicable.
<b>MARINE POLLUTANT</b>	: D-limonene: Dipentene,
<b>EMERGENCY RESPONSE GUIDE</b>	: ERG# 128

# SAFETY DATA SHEET

## SPOTMASTER GEL XP

### SECTION 15 – REGULATORY INFORMATION

**U.N. GHS CLASSIFICATION & LABELING INFORMATION:** See Section 2 for GHS Hazard Information.

**U.S. FEDERAL REGULATORY INFORMATION:**

**LISTED CARCINOGEN** : Not listed.  
**TSCA STATUS** : The ingredients of this product are listed in TSCA inventory (40CFR 710.)  
**SARA SECTION 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.  
**SARA SECTION 312** : Dipropylene Glycol Methyl Ether : Chronic health hazard  
Isopropanol : Acute health hazard, Chronic health hazard, Fire hazard.  
**SARA SECTION 313** : The following components are subject to reporting levels established by SARA title III, Section 313: ISOPROPANOL (CAS# 67-63-0)  
**CERCLA** : 5000 LBS. (2270 kg) as Acetone 100%  
**NFPA HEALTH** : 2  
**NFPA FLAMMABILITY** : 2  
**NFPA REACTIVITY** : 0

**EUROPEAN UNION REGULATORY INFORMATION:**

**EC CLASSIFICATION** : Flammable, Irritant  
**DSD/DPD RISK (R) PHRASES** : R11: Highly flammable. (Isopropanol)  
R22: Harmful if swallowed.  
R36: Irritating to skin.  
R67: Vapors may cause drowsiness and dizziness.  
**DSD/DPD SAFETY (S) PHRASES** : S2: Keep out of reach of children.  
S7: Keep container tightly closed.  
S16: Keep away from sources of ignition – No smoking  
S24/25: Avoid contact with eyes and skin.  
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
S36/S37/39: Wear suitable protective clothing, gloves and eye/face protection.  
S45: In case of accidents or if you feel unwell, seek medical advice immediately. Show label where possible.  
S61: Avoid release to the environment.  
S62: If swallowed, do not induce vomiting.  
S64: If swallowed, rinse mouth with water if victim is conscious.  
**DSD/DPD HAZARD SYMBOL** : F: Flammable, Xi: Irritant



**CANADIAN REGULATORY INFORMATION:**

**WHMIS CATEGORY** : Acetone & Isopropanol: B2: Flammable Liquid  
: Isopropanol: D2B: Materials that cause other toxic effects (TOXIC).  
**DOMESTIC SUBSTANCES LIST (DSL)** : Listed  
**INGREDIENT DISCLOSURE LIST** : Listed



### SECTION 16 – OTHER INFORMATION

**DISCLAIMER** : The information contained herein has been compiled from sources believed to be

## **SAFETY DATA SHEET**

### **SPOTMASTER GEL XP**

reliable and accurate to the best of our knowledge at this date. It is provided without warranty, expressed or implied, as to the results of use of this information or to the product to which it relates. Hydramaster Corp. assumes no responsibility for injury to any person or property resulting from any use of the material. Each user assumes the risk in their use of this product and should review the data and recommendations in the specific context of their intended use.

<b>CERCLA</b>	: Comprehensive Environmental Response, Compensation, and Liability Act.
<b>EINECS</b>	: European Inventory of Existing Commercial Chemical Substances
<b>IMDG</b>	: International Maritime Code for Dangerous Goods
<b>IARC</b>	: International Agency for Research on Cancer
<b>IATA</b>	: International Air Transportation Association
<b>ACGIH</b>	: American Conference of Governmental Industrial Hygienists
<b>NFPA</b>	: National Fire Protection Association (USA)
<b>NTP</b>	: National Toxicology Program
<b>SARA</b>	: Superfund Amendments and Reauthorization Act
<b>TSCA</b>	: Toxic Substances Control Act
<b>HMIS</b>	: Hazardous Materials Identification System (USA)
<b>WHMIS</b>	: Workplace Hazardous Materials Information System
<b>LC50</b>	: Lethal concentration, 50 percent
<b>LD50</b>	: Lethal dose, 50 percent
<b>STOT</b>	: Systemic Target Organ Toxicity
<b>DATE PREPARED</b>	: JAN 2, 2013
<b>DATE REVISED</b>	: JAN 2, 2015