

WoolMaster™

Rug and Fabric Preconditioner



- » **CleanMaster** is pleased to provide you with a preconditioner/prespray specifically formulated to safely and effectively clean Oriental Rugs, Wool Rugs, Carpet, and Fabric; natural and cotton fiber rugs and fabric; and other investment textiles.
- » **WoolMaster** combines specialized encapsulation surfactants, detergents, and conditioning agents to specifically target the soils that rugs and fabrics are commonly exposed to.
- » Most “wool” and “fine fabric” cleaning agents are just pH reduced carpet prespray formulations or old shampoo formulas. **WoolMaster** brings state of the art technology to cleaning investment textiles.

*If for any reason you are not thrilled with the performance of **WoolMaster** return it to your distributor and we'll get you a product that does.*



Directions: Pre-Cleaning Procedures for all Rugs:

1. Read entire label before using. Use only as directed.
2. Carefully pre-inspect the rug, fabric, or carpet before proceeding. Identify fiber content, construction, dye stability, shrinkage considerations, and pre-existing damage. Always test every rug for dye bleeding potential. Carefully look for conditions which could contribute to cleaning related challenges such as pre-existing pet urine, water damage, fiber deterioration, past cleaning residues, and fringe discoloration. Follow industry recommended cleaning procedures and standards of care.
3. The preferred method for cleaning investment textile rugs is in-plant.
4. If cleaning on-location, work area preparation must include:
 - a. Make sure there is adequate airflow for drying and ventilation.
 - b. Adequate and safe work area where you can safely move the required cleaning equipment and tools around and the rug can be safely cleaned on the floor without causing damage to or from other surfaces which might bleed color when moist or wet.
 - c. Always keep white, cotton, colorfast towels handy to wipe up any cleaning solution overspray which may get on other surfaces
5. Prior to wet cleaning, remove as much dry soil as possible from the rug utilizing a vacuum (with a beater bar), portable rug dusting unit, compressed air system, or automated duster. Follow equipment manufacturer directions.

On-Location Cleaning:

1. Follow all Pre-Cleaning Procedures
2. **WoolMaster** should be used as a preconditioner for soiled rugs.
3. a. For use with Pump/Electric Sprayers: Mix 6 oz. of **WoolMaster** with 1 gallon hot water (1 to 24). For exceptionally heavy soil, mix 8 oz of solution per gallon of water (1-16). Spray until carpet or fabric is damp. Do not allow carpet or fabric to dry before extraction.
4. b. For use with In-Line Injection Sprayer: For use with regular 1-8 Hydro-Force Pro Sprayer, mix 1 part **WoolMaster** to 2 parts water in 5 quart container. Apply evenly across carpet. Do not over-apply solution. Do not allow carpet to dry before extraction.
5. For extraction rinse, mix **RinseOut** in solution tank of extraction unit according to the following directions:
 - a. Portable extractor: Mix 2 oz of solution to 5 gallons of water in extraction tank.
 - b. Truckmount: Mix 1 quart solution (32 oz) with 5 gallons of water into solution container. Set solution flow meter between 2 and 3.
6. Cleaning fringes constructed of cotton fiber may require special solutions and cleaning application utilizing **HydraBoost CT**. Proceed to Fringe cleaning procedures if necessary.
9. Speed dry utilizing axial, downdraft or centrifugal air movers
10. Groom or brush as needed

See the material safety data sheet at www.cleanmaster.com for safety and regulatory information.

Learn more,
scan here



Available in: 1 Gallon; Case of 4 x 1 Gallon

Part number: 950-242-S, B

11015 47th Ave W, Mukilteo, WA 98275

www.cleanmaster.com • 877.282.2319

CLEANMaster
HydraMaster Cleaning Solutions

